

REMARKS

In the Specification

The Office Action indicates that the specification does not enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to use the invent incommensurate in scope with the claims. I submit herewith a substitute specification. Also accompanying this amendment is a reproduction of the original specification with markings indicating the amendments effected in the substitute specification. No new matter is entered. Reconsideration of the rejection of the specification is earnestly requested.

In the Claim

Claims 1 - 4 are now in this application. Claims 1 – 4 are rejected.

Claims 1 – 4 are rejected based on a quotation of the second paragraph of 35 U.S.C.

112.

The Office Action indicates that the claims are narrative in form and replete with indefinite and function or operational language; the structure that goes to make up the device must be clearly and positively specified; the structure must be organized and correlated in such a manner as to present a complete operative device; and the claims must be in one sentence form only. Therefore, I submit the amended claims as the Examiner requested. The claims are amended to clarify the present invention and to remove or correct phraseology. No new matter is entered. Reconsideration of the rejection of the claims and their allowance are earnestly requested.

Claims 1, 3 and 4 are rejected under 35 U.S.C. 102 (b) as being anticipated by Hines et al. I herein respectfully traverses these rejections.

For the rejections to be sustained under 102 (b) each and every element of the

claimed invention must be disclosed in the cited prior art reference. It is respectfully submitted that the cited reference fails to disclose at least the following features and elements of the present invention as noted herein.

Independent claim 1 recites in pertinent part the following:

“a receipt object formed in a shape of a sheath, capable of carrying
and storing the protective tool into a space thereinto so as to wrap,
having a drawing-out part, provided at a surface of the receipt object, which
can reduce the frictional resistance when the protective tool is pulled out”

Hines et al. fails to disclose a drawing-out part formed at a surface of the receipt object when the protective tool is pulled out. The feature absent from the cited reference.

Claims 3 and 4 are amended to depend from claim 1 and therefore also include that missing element. Therefore, reconsideration of the rejection of the claim 1, 3 and 4 and their allowance are respectfully requested.

Claim 2 is amended to depend from claim 1. Therefore, reconsideration of the rejection of the claim 1, 3 and 4 and their allowance are respectfully requested.

In the Abstract

A replacement abstract is provided herein on a separate page. It is submitted that the replacement abstract is in full. No new matter is added.

In light of forgoing, I am now believed to be in proper form for allowance of all claims and notice to that effect is earnestly solicited.

Respectfully submitted,

Atsushi Tai

Enc: Substitute Specification, Marked reproduction of original specification and
Amended claims



MARKED UP SPECIFICATION

PROTECTIVE IMPLEMENT

5 BACKGROUND OF THE INVENTION

The present invention relates to a protective implement, especially the protective implement which is carried without touching the eyes of the general public, and which can be used on user's toes in an instant in an emergency.

10 The conventional protective implement, especially the nightstick is formed in the shape of a stick made of the metallic, wooden and resin with the fixed length or flexible length, and this is mainly used for the policemen, guards, etc.

Since the conventional nightstick is used for guard duties, there is a problem in appearance, weight, and the maintenance system for carrying for self-defense in the
15 general public. In appearance, the nightstick in fixed length cannot bring every day, and the flexible nightstick also has about 20 to 30 cm in the full length when it is expanded and it is difficult to bring it every day. Also the weight is 500 g or more and its weight is too heavy in order to bring everyday without being conscious. In carrying, the exclusive holder equipped with a belt and bag is used. However, the holder is easy to be watched
20 by other people in the public and the shape of dignity of the holder is not good since ordinary persons spend the usual social life. In use, since it is a metal stick, when a partner's head is hit, you may make it die. Therefore, it is not the self-defense purpose and it is very dangerous when it is used as a weapon.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a protective implement that can always carry without worrying about its weight, needing special
5 consideration to appearance, the carrying method and the public notice for self-defense to the ordinary persons. Also it is another object of the present invention to provide a protective implement that can attain the self-defense purpose in an instant in emergency.

The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages
10 thereof, are described below with reference to the accompanying drawings in which a presently preferred embodiment of the invention is illustrated as an example.

It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only, and are not intended as a definition of the limits of the invention.

BRIEF DESCRIPTION OF THE DRWINGS

FIG. 1 is an explanation view showing a first embodiment of the present invention;

FIG. 2 is an exploded view showing a first embodiment of the present invention;

20 FIG. 3 is a front view of a grip part of protective tool showing a first embodiment of the present invention;

FIG. 4 is a side view of a grip part of protective tool showing a first embodiment of the present invention;

FIG. 5 is a bottom view of a grip part of protective tool showing a first

embodiment of the present invention;

FIG. 6 is a cross sectional view taken along a line 6 – 6 of FIG. 2;

FIG. 7 is a cross sectional view taken along a line 7 – 7 of FIG. 2;

FIG. 8 is an explanation view showing the way in which a protective implement is

5 installed;

FIG. 9 is an explanation view showing the way in which the user hooks with a ring;

FIG. 10 is an explanation view showing the way in which a protective tool is pulled;

10 FIG. 11 is an explanation view showing a second embodiment of the present invention;

FIG. 12 is an explanation view of a grip part of protective tool showing a second embodiment of the present invention;

15 FIG. 13 is an explanation view showing a third embodiment of the present invention;

FIG. 14 is a cross sectional view taken along a line 14 – 14 of FIG. 13;

FIG. 15 is an explanation view showing a fourth embodiment of the present invention;

FIG. 16 is an explanation view when in use;

20 FIG. 17 is an explanation view showing a fifth embodiment of the present invention;

FIG. 18 is an explanation view when in use;

FIG. 19 is an explanation view when in use in a sixth embodiment of the present invention; and

FIG. 20 is a cross sectional view taken along a line 20 – 20 of FIG. 19.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Preferred embodiments of the present invention are described in more detail below referring to the accompanying drawings.

FIGS. 1 to 11 illustrate a protective implement of a first embodiment of the present invention. The numeral 1 shows a protective implement, a belt as the protective implement in this embodiment [,]. [and as] As illustrated in FIG. 1 and FIG. 2, the belt 1
10 as the protective implement includes a receipt object 2 for a protective tool formed in the shape of a belt and [the] a protective tool 3 [formed] with [the] a steel wire with [stiff] certain stiffness carried into the receipt object 2 so as to wrap [around].

As illustrated in FIG. 2, the receipt object 2 further includes a receipt object body 4 formed in the shape of a sheath and a drawing-out [parts] part 5 formed in the shape of a
15 slit, formed in the back part of the receipt object body 4 [at the time of] when in wearing, carrying the protective tool 3 thereinto and reducing the frictional resistance when in drawing out.

Therefore, both ends of the receipt object body 4 are formed in the shape of a flap respectively by divided by the drawing-out part 5.

20 The receipt object body 4 in the shape of the sheath has a space thereinto at a hollow state to the length direction that is balanced the full length of the protective tool 3. It is formed 3 to 5 mm in thickness, preferably in 4mm and formed 8 to 12 mm in the width direction, preferably 10 mm. Moreover, a reinforcement plate 6 is laid under the internal part of the receipt object body 4 so that the protective tool 3 may draw out and

leather of the outside of the belt may not be damaged when in drawing or storing it. Also the reinforcement plate 6 for model collapse prevention of the belt is laid under the part that similarly touches a tip portion of the protective tool and the part at the middle of the belt.

5 The drawing-out part 5 provides the flaps at a surface of the receipt object body4.

The tip part of the drawing-out part 5 has applied and sutured a patch 7 in order to prevent a crack for reinforcement. Another end of the drawing-out part 5 is formed a storing part 8 formed in the shape of a square, a round shape etc. which cut off leather in square form in this embodiment so that the end of the protective tool 3 may tend to be
10 settled.

The drawing-out part 5 as the slit is formed the tip portion to the end portion of the receipt object body 4. The drawing-out part 5 can let go and disperse the power of the frictional resistance, and it can prevent to break inside the receipt object body 4.

As illustrated in FIG. 2, the protective tool 3 further includes a [nightstick]
15 protective tool body 9 formed with the steel wire with [stiff] stiffness and a grip part 10 attached rotatably in the end of the [nightstick] protective tool body 9 so as to be contained by the drawing-out part 5 of the receipt object 2 at the optimal state during in receipt so that the drawing-out is comfortably done when in drawing-out. The steel wire as the nightstick body 9 is [given with stiff by using] used MULTIPLE WIRE TYPE
20 CONSTRUCTION 7 X 7 with a diameter of several mm preferably. [This] It has the hardness and suppleness that suited on the fiber structure of a wire. Moreover, although a difference makes it according to a practical use form, there is about 60 cm as standard in full length. Moreover, the tip part of the [nightstick] protective tool body 9 is fixed with plasma melting processing, solder, etc. so that it can hold together.

In addition, in this embodiment, the tip part of the [nightstick] protective tool body 9 is put the cap thereon and fixed so that it can hold together.

The grip part 10 further includes a grip part body 11 attached rotatably in the end of the [nightstick] protective tool body 9 and a ring 12 for drawing out the [nightstick]
5 protective tool body 9 attached rotatably in the end of the grip part body 11. Since the ring 12 is stored inside the receipt object 2 in receipt, nobody can see it and it is not visible from outside.

As illustrated in FIG. 1, in receipt, the protective tool 3 is contained into the receipt object 2 and is let pass, and it is used for trousers as usual.

10 As illustrated in FIG. 8 to FIG. 10, when in use, by locating a ring 12 into the receipt object 2 and hanging a finger on the ring 12 and drawing out to a forward direction or downward direction, the [nightstick] protective tool body 9 is pulled out besides the receipt object 2, dividing the drawing-out part 5 simultaneously with starting a drawing-out operation, as illustrated in FIG. 7. That is, the protective tool 3 can be
15 drawn out smoothly without damaging the receipt object 2 because the mighty frictional resistance by drawing out produced between the [nightstick] protective tool body 9 and the receipt object 2 is changed into the energy which divides [a contact] the surface of the receipt object 2 [with] by the drawing-out part 5.

Other embodiments of the present invention will now be described referring to
20 Figs. 11 to 20. Through the drawings of the embodiments, like components are denoted by like numerals as of the first embodiment and will not be further explained in great detail.

A second embodiment of the present invention is shown in Figs. 11 and 12. It is distinguished from the first embodiment by the fact that the grip part 10 is put on the end

of the [nightstick] protective tool body 9 and fixed. A protective implement 1A with the protective tool 3A according to the second embodiment has similar advantages to that according to the first embodiment.

5 A third embodiment of the present invention is shown in Figs. 13 and 14. It is distinguished from the first embodiment by the fact that an implement receipt object body 4A without the drawing-out part 5 is used. A protective implement 1B with a receipt object 2A can contain the protective tool 3 therein without spoiling a design.

10 A fourth embodiment of the present invention is shown in Figs. 15 and 16. It is distinguished from the first embodiment by the fact that a receipt object body 4B formed in the shape of a strap, which is used for a shoulder bag, briefcase 13 or the like, is used. A protective implement 1C with a receipt object 2A according to the fourth embodiment has similar advantages to that according to the first embodiment.

15 A fifth embodiment of the present invention is shown in Figs. 17 and 18. It is distinguished from the third embodiment by the fact that a receipt object body 4C sewn on the side part inside the trousers fabricated by cloth thick including jeans cloth and leather, a jean 14 in this embodiment is used. A protective implement 1D with a receipt object 2C according to the fifth embodiment has similar advantages to that according to the third embodiment.

20 In addition, the receipt object body 4C of the protective implement 1D may be formed in the side part of the jeans 14 integrally.

A sixth embodiment of the present invention is shown in Figs. 19 and 20. It is distinguished from the third embodiment by the fact that a receipt object body 4D prepared in the skirt slippage part of the coat fabricated by cloth thick including jeans cloth and leather, a jacket 15 of the jeans cloth in this embodiment integrally is used. A

protective implement 1E with the receipt object 2D according to the sixth embodiment has similar advantages to that according to the third embodiment

In addition, the receipt object body 4D of the protective implement 1E may be sewn on the skirt slippage part of the jacket 15 as another object and may be used.

5 Furthermore, although each embodiment differs mainly explained based on the first embodiment, even if it uses the present invention combining the composition used for the form of not only this but each embodiment, the same action effect is acquired.

As set forth above, the advantages of the invention are as follows:

(1) A protective implement comprises a protective tool formed with a steel wire
10 [with stiff; and a receipt object, capable of carrying the protective tool so as to wrap around, having a drawing-out part which can reduce the frictional resistance during in drawing out] ; and a receipt object formed in a shape of a sheath, capable of carrying and storing the protective tool into a space thereinto so as to wrap, having a drawing-out part, provided at a surface of the receipt object, which can reduce the frictional resistance when
15 the protective tool is pulled out so that it can always carry without being afraid of the public notice and special consideration to its weight and the carrying method, and a self-defense system can be taken in an emergency in an instant.

(2) As discussed above, when in use, while it has a sufficient power for repulsing a rowdy, when a partner is immature youth, it can carry out consideration that there is no
20 fear of giving a mortal wound and it dies more than achievement to defend self.

(3) As discussed above, it can be used by the same fine sight as usual without spoiling a design.

(4) As discussed above, since the structure is simple, it can carry out easily.

Therefore, it can manufacture cheaply.

CLAIMS AMENDMENT

Please amend the claims as rewritten below.

1. (Currently Amended) A protective implement comprising:
a protective tool formed with a steel wire[with stiff]; and
a receipt object formed in a shape of a sheath, capable of carrying and storing the protective tool into a space thereinto so as to wrap [around], having a drawing-out part, provided at a surface of the receipt object, which can reduce the frictional resistance [at the time of drawing] when the protective tool is pulled out.

2. (Currently Amended) A protective implement according to claim 1, wherein the protective tool further includes a [nightstick] protective tool body [formed] with [a] the steel wire [with stiff] and a grip part attached rotatably in an end of the [nightstick] protective tool body so as to be contained at an optimal state during in receipt into the receipt object body.

3. (Currently Amended) A protective implement according to claim 1, wherein the receipt object further includes a receipt object body formed in the shape of a sheath and a drawing-out part formed in the [contact] surface of the protective tool and in the shape of a slit, capable of carrying and storing the protective tool into a space thereinto so as to wrap [around], reducing a frictional resistance [during in drawing-out] when the protective tool is pulled out.

4. (Currently Amended) A protective implement according to claim 1, wherein the receipt object is provided in one of a skirt part of a coat formed by cloth including jeans cloth and leather [,] and a side part slippage of an inner side part of trousers [one of integrally and as another object].

ABSTRACT AMENDMENT

Please replace the abstract with the substitute abstract submitted on the following separate page.